

HD-IP IR PTZ SPEED DOME: HK-SD2FD20X-5M

- * Support P2P function, H.265
- * 2MP/5MP, 20X/36X Zoom is optional
- * 4.5" Half Metal Body Construction, IP66
- * ONVIF ; Compatible with HIKVISION, DAHUA, Raysharp, TVT, AEVISION NVR etc
- * Intelligent IR illumination & power consumption is variable, dependant the zoom factor
- * Built-in Hikvision Protocol



Specification

Camera	
MODEL	HK-SD2FD20X-5M
Sensor	GK7205V300 + SONY335
Output pixel	5MP 2592*1944
Lens	20X f=4.7mm~96.3mm
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
DNR	2DNR,3DNR
WDR	DWDR
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTC P, NTP
Software Control	IE, IPC ModuleTool, IVS365
Rotation Range	Pan: 0°~360° , Tilt: 0°~93°
Rotation Speed	Pan: 0~80°/s , Tilt:0~40°/s
Auto Flip	Horizontal 180°, Vertical 93°
Preset Points	220pcs presets (dwell time 01-60s interval available)
A-B scan	User programmabel(scan speed 1-64 levels setting available)
Guard Tours	3 groups(Max.16 points, dwell time user selectable)
Operating temperature	-40°~+60°C
Operation menu	English
Power	DC 12V
Consumption	≤15W
Related validation	IP66
IR distance	Up to 60 meters
LEDs	6PCS IR LED