

HD-IP IR PTZ SPEED DOME: HK-SD2HK20X-5M

- * Support P2P function
- * 7" Half Metal Body Construction, IP66
- * Optional function: POE
- * Intelligent IR illumination & power consumption is variable, dependant the zoom factor
- * Built-in Hikvision Protocol



Specification

Camera	
MODEL	HK-SD2HK20X-5M
Solution	GK7205V300 + SONY335
Output Pixel	5MP 2560*1920
Lens	20X f=4.35mm~96.3mm
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
DNR	2DNR,3DNR
WDR	DWDR
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTC P, NTP
Software Control	IE, IPC ModuleTool, IVS365
Rotation range	Pan:0~360°,Tilt:0~93°
Rotation speed	Pan: 0~80°/s , Tilt:0~40°/s
Auto Flip	Horizontal 180°,Vertical 93°
Preset Points	220pcs presets(dwell time 01-60s interval available)
A-B scan	User programmable(scan speed 1-64 levels setting available)
Guard Tours	3 Groups(Max.16 points, dwell time user selectable)
Operating temperature	-40°C~+60°C
Operation menu	English
Power	DC 12V/POE(Optional, 802.3at)
Consumption	≤25W
Related validation	IP66
IR Parameters	
Auto Control IR LED	PWM
LEDs	Up to 150M
IR distance	6PCS IR LEDs+2PCS Laser LEDs