

HD-IP IR PTZ SPEED DOME: HK-SD2IF20X-2M

- * Support P2P function,H.265
- * 7" Full Metal Body Construction, IP66
- * 8 PCS IR Led+4 PCS Laser Led, IR range up to 150M
- * Intelligent IR illumination & power consumption is variable, dependant the zoom factor
- * Built-in Hikvision Protocol



Specification	
Camera	
MODEL	HK-SD2IF20X-2M
Sensor	GK7205V200 + GC2063
Output pixel	2MP 1920*1080
Lens	20X f=4.7mm~96.3mm 36X f=4.6mm~167mm
BLC	Support
AGC	Auto/Manual
WB	Indoor/Outdoor/Auto/Manual
DNR	2DNR, 3DNR
WDR	DWDR
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTC P, NTP
Software Control	IE, IPC ModuleTool, IVS365
Mobile View(optional)	Android , iPhone
Rotation range	Pan:0~360°,Tilt:0~93°
Rotation speed	Pan: 0~80°/s , Tilt:0~40°/s
Auto Flip	Horizontal 180°,Vertical 93°
Preset Points	220pcs presets (dwell time 01-60s interval available)
A-B scan	User programmabel(scan speed 1-64 levels setting available)
Guard Tours	3 groups(Max.16 points, dwell time user selectable)
video compression	H.265/M-JPEG
Operating temperature	-40°C~+60°C
Operation menu	English
Power	DC 12V
Consumption	≤25W
Related validation	IP66
IR Parameters	
Auto Control IR LED	PWM
LEDs	8 PCS IR Led+4 PCS Laser Led
IR distance	IR range up to 150M