

# HD-IP IR PTZ HIGH SPEED DOME: HK-SD2IK36X-5M

- \* 7inch, Half Metal Body Construction, IP66
- \* IR distance 150 meters (6pcs IR LED+2pcs Laser LED)
- \* Support P2P function, ONVIF, H.264/H.265/MJPEG
- \* Intelligent IR illumination & power consumption is variable, dependant the zoom factor
- \* Compatible with HIKVISION ,DAHUA, XM NVR etc.
- \* Guard Tours: 3Group, Preset Points: 220PCs
- \* Optional function: POE, AC24V
- \* Built-in Hikvision Protocol



## Specification

Camera			
MODEL	HK-SD2IK36X-5M		
Solution	GK7205V300 + SONY335		
Output Pixel	5MP 2560*1920		
Lens	20X f=4.35mm~96.3mm	20X f=4.35mm~96.3mm	36X f=4.6mm~165mm
BLC	Support		
AGC	Auto/manual		
WB	Auto/manual/indoor/outdoor		
DNR	2DNR, 3DNR		
WDR	DWDR		
S/N Ratio	≥50dB		
Dome			
Communications Protocol	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTC P, NTP		
Software Control	IE, IPC ModuleTool, IVS365		
Rotation range	Pan:0~360°,Tilt:0~93°		
Rotation speed	Pan: 0~200°/s , Tilt:0~100°/s		
Auto Flip	Support		
Preset Points	220pcs presets(dwel time 01-60s interval available)		
A-B scan	User programmabel(scan speed 1-64 levels setting available)		
Guard Tours	3 Groups(Max.16 points, dwell time user selectable)		
Operating temperature	-40°C~+60°C		
Operation menu	English		
Power	DC 12V/POE(Optional, 802.3at)		
Consumption	≤25W		
Related validation	IP66		
IR Parameters			
Auto Control IR LED	PWM		
LEDs	Up to 150M		
IR distance	6PCS IR LEDs+2PCS Laser LEDs		