



MODEL:HK-XVR8108F

Feature:

- Support H.265+ encoding, ultra-low bitrates, compatible with H.264 surroundings;
- Support VGA, HDMI full HD output simultaneously;
- Support ONVIF; access third party;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support various mobile monitoring (iPhone, Android);
- Remote Access, With DNS (ARSP),easy to monitor remotely
- Support UTC, control signal& video stream transmit through one single coaxial
- Support XVI/AHD/TVI/CVI/CVBS/IP six signals;
- Support intelligent analysis: functions like Perimeter alert、 item retention、 Video diagnosis、 intelligent fast play and intelligent retrieval

Specification:

	Model	HK-XVR8108F
System	Main processor	Hi3531D
Interface	Preview	1/4/8/9
Video	Codec	H.265+/H.265/H.264+/H.264
	Monitor quality	VGA(1080P at most);HDMI(4K at most)
	Preview ability	8*8M@15fps(AHD)/8*5M@20fps (6 in 1) /8*4M (6 in 1)
	Encode ability	8*8M@8fps (AHD) /8*5M@14fps (6 in 1) / 8*4M@18fps (6 in 1) /8*3M@21fps (6 in 1) /8*1080P(6 in 1)
	Decode ability	4*8M@8fps (AHD) /8*5M@14fps (6 in 1) / 8*4M@18fps (6 in 1) /8*3M@21fps (6 in 1) /8*1080P(6 in 1)
	Multi-mode input	analog: 8*8M;8*5M; Digital to analog conversion: support (except 8+8 hybridmode) hybrid: 8*5M (analog) +8*5M (network) 4*5M (analog) +4*5M (network) network: 8*3M ;4*5M
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	8ch(analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	8ch BNC
	Video output	1ch VGA, 1ch HDMI
	Loop Vout	N/A
	Audio I/O	4(Can be extended to 8ch)/1

	Alarm I/O	0 (Can be extended to 4ch) /0 (Can be extended to 1ch)
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	1*RS485, Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	1*SATA ports (Max 8TB/per)
	Wireless	3G, WIFI (extend via USB)
General	Power supply	12V/4A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0℃—+55℃, Humidity:10%—90%, Atm:86kpa—106kpa
	Dimension	
	Weight	